



# Business Machine

## Single Wide Wheel / Heavy Duty Capacity to 700 pounds each

### FEATURES

- ✓ **Design:** low profile design for lower equipment height.
- ✓ **Finish:** bright zinc plating to resist rust and corrosion.
- ✓ **Swivel Construction:** durable double ball raceway.
- ✓ **Axle:** 3/8" diameter nut & bolt.

### CASTER OPTIONS

- ✓  **Hex Head Brake:** to order, add "HHBRK" to end of caster model number.
- ✓  **Thumb Screw Brake:** to order, add "TSBRK" to end of caster model number.
- ✓ **Optional plates and stems:** wide variety available—consult factory.



**3-61-532**  
(shown in photo)

### Swivel Top Plate

Wheel Diameter (Inches)	Tread Width (Inches)	Wheel Type	Bearing	Capacity (Pounds)	Swivel Plate Model Number	Load Height (Inches)	Swivel Radius (Inches)
3	1 13/16	POLYOLEFIN PHENOLIC	ROLLER ROLLER	500 700	3-61-532 3-61-222	4 5/16	3

**Top Plate Size:** 3-1/8" x 4-1/8" • **Bolt Hole Centers:** 2-3/8" x 3-3/8" •  
**Mounting Bolt Size:** 3/8" diameter



**3-62-532**  
(shown in photo)

### Rigid Top Plate

Wheel Diameter (Inches)	Tread Width (Inches)	Wheel Type	Bearing	Capacity (Pounds)	Rigid Plate Model Number	Load Height (Inches)	Swivel Radius (Inches)
3	1 13/16	POLYOLEFIN PHENOLIC	ROLLER ROLLER	500 700	3-62-532 3-62-222	4 5/16	N/A

**Top Plate Size:** 3-1/8" x 4-1/8" • **Bolt Hole Centers:** 2-3/8" x 3-3/8" •  
**Mounting Bolt Size:** 3/8" diameter