

# PRIMACY COVER (PC)

FREE SWIVEL •  
TOTAL LOCK •  
TOTAL/DIRECTION  
LOCK COMBO

**NEW**



## APPLICATIONS

- Hospital Beds
- Stretchers
- Ultrasonic Equipment
- Care Beds
- Intensive Care Beds

## FEATURES

- Improved braking system in swivel and wheel
- Precision bearings in wheels
- TPR cover in one-piece design
- Caster meets ISO Standard 22882: 2004 Caster & Wheels - Requirements for Casters for Hospital Beds.
- Very Positive swivel lock that operates independently of the wheel brake, reducing wear and tendency to ratchet
- Wheel brake can be applied dynamically without damage to mechanism.
- Factory-set mechanism, maintenance-free for the life of the caster;
- Stem with M8 fixing holes to suit all bed layouts and reduce stock holding.

Antistatic option available. Consult Factory.

### CENTRAL LOCKING TOTAL LOCK MODELS

Wheel Diameter mm (in)	Tread Width mm (in)	Wheel Description	Capacity (Lbs)	Load Height mm (in)	Swivel Radius mm (in)	Wheel Bearing	Model Number
100 (4)	30 (1-1/4)	Thermoplastic Rubber	220	133 (5-8/32)	92 (3-5/16)	Precision Ball	PC-04TPP-125-TL-CL__
100 (4)	30 (1-1/4)	Polyurethane TPU	220	133 (5-8/32)	92 (3-5/16)	Precision Ball	PC-04PYP-125-TL-CL__
125 (5)	32 (1-1/4)	Thermoplastic Rubber	220	158 (6-3/16)	107 (4-3/16)	Precision Ball	PC-05TPP-125-TL-CL__
125 (5)	32 (1-1/4)	Polyurethane TPU	220	158 (6-3/16)	107 (4-3/16)	Precision Ball	PC-05PYP-125-TL-CL__
150 (6)	32 (1-1/4)	Thermoplastic Rubber	264	184 (7-1/4)	126 (4-15/16)	Precision Ball	PC-06TPP-125-TL-CL__
150 (6)	32 (1-1/4)	Polyurethane TPU	264	184 (7-1/4)	126 (4-15/16)	Precision Ball	PC-06PYP-125-TL-CL__
200 (8)	32 (1-1/4)	Thermoplastic Rubber	264	237 (9-5/16)	161 (6-5/16)	Precision Ball	PC-08TPP-125-TL-CL__
200 (8)	32 (1-1/4)	Polyurethane TPU	264	237 (9-5/16)	161 (6-5/16)	Precision Ball	PC-08PYP-125-TL-CL__


### CENTRAL LOCKING DIRECTIONAL AND TOTAL LOCK COMBO

100 (4)	30 (1-1/4)	Thermoplastic Rubber	220	133 (5-8/32)	92 (3-5/16)	Precision Ball	PC-04TPP-125-DT-CL__
100 (4)	30 (1-1/4)	Polyurethane TPU	220	133 (5-8/32)	92 (3-5/16)	Precision Ball	PC-04PYP-125-DT-CL__
125 (5)	32 (1-1/4)	Thermoplastic Rubber	220	158 (6-3/16)	107 (4-3/16)	Precision Ball	PC-05TPP-125-DT-CL__
125 (5)	32 (1-1/4)	Polyurethane TPU	220	158 (6-3/16)	107 (4-3/16)	Precision Ball	PC-05PYP-125-DT-CL__
150 (6)	32 (1-1/4)	Thermoplastic Rubber	264	184 (7-1/4)	126 (4-15/16)	Precision Ball	PC-06TPP-125-DT-CL__
150 (6)	32 (1-1/4)	Polyurethane TPU	264	184 (7-1/4)	126 (4-15/16)	Precision Ball	PC-06PYP-125-DT-CL__
200 (8)	32 (1-1/4)	Thermoplastic Rubber	264	237 (9-5/16)	161 (6-5/16)	Precision Ball	PC-08TPP-125-DT-CL__
200 (8)	32 (1-1/4)	Polyurethane TPU	264	237 (9-5/16)	161 (6-5/16)	Precision Ball	PC-08PYP-125-DT-CL__


### CENTRAL LOCKING FREE SWIVEL MODELS

100 (4)	30 (1-1/4)	Thermoplastic Rubber	220	133 (5-8/32)	92 (3-5/16)	Precision Ball	PC-04TPP-125-SW-RS__
100 (4)	30 (1-1/4)	Polyurethane TPU	220	133 (5-8/32)	92 (3-5/16)	Precision Ball	PC-04PYP-125-SW-RS__
125 (5)	32 (1-1/4)	Thermoplastic Rubber	220	158 (6-3/16)	107 (4-3/16)	Precision Ball	PC-05TPP-125-SW-RS__
125 (5)	32 (1-1/4)	Polyurethane TPU	220	158 (6-3/16)	107 (4-3/16)	Precision Ball	PC-05PYP-125-SW-RS__
150 (6)	32 (1-1/4)	Thermoplastic Rubber	264	184 (7-1/4)	126 (4-15/16)	Precision Ball	PC-06TPP-125-SW-RS__
150 (6)	32 (1-1/4)	Polyurethane TPU	264	184 (7-1/4)	126 (4-15/16)	Precision Ball	PC-06PYP-125-SW-RS__
200 (8)	32 (1-1/4)	Thermoplastic Rubber	264	237 (9-5/16)	161 (6-5/16)	Precision Ball	PC-08TPP-125-SW-RS__
200 (8)	32 (1-1/4)	Polyurethane TPU	264	237 (9-5/16)	161 (6-5/16)	Precision Ball	PC-08PYP-125-SW-RS__

#### Locking Models




- Stem diameter 27.8mm
- Two locking hole options
- Locking hole in line or across direction of travel
- Four fixing holes
- Snap-on adapter sleeves options for different tube dimensions
- Standard cam (41°/52°)



- Stem diameter 32mm
- Two locking hole options available
- Locking hole in line or across direction of travel
- Four fixing holes
- Standard cam 30°


Steering  
(locks swivel)



#### Free Swivel Models



RS03  
27.8mm x 45mm  
for tubular frame  
with 28mm ID



RS05  
32mm x 45mm  
For tubular frame  
with 32mm ID

