

PREVAIL LOW PROFILE TWIN WHEEL (PL)

FREE SWIVEL • TOTAL LOCK • TOTAL/DIRECTION LOCK COMBO

NEW



- APPLICATIONS**
- Hospital Beds
 - Stretchers
 - Mobile Ultrasound Equipment
 - Radiology Tables
 - Medical Chairs/Recliners
 - ICU Beds
 - Care Beds

- FEATURES**
- Smooth Integrated Central Locking Selection for free Swivel, Total Lock, and Directional (steer) Lock
 - Precision Bearings in Swivel Section and Sealed Precision Bearings in wheels.
 - Durable Twin Non-marking Polyurethane wheel treads
 - Washable - Easy to clean and Disinfect with detergents and cleaning agents
 - Antistatic Option Available
 - TUV Certified
 - Caster meets ISO Standard 22882 - EN 12531 Caster & Wheels - Requirements for Casters for Hospital Beds

CENTRAL LOCKING TOTAL LOCK MODELS

Wheel Diameter mm (in)	Tread Width mm (in)	Wheel Description*	Capacity (lbs)	Load Height mm (in)	Swivel Radius mm (in)	Wheel Bearing	Model Number
125 (4-21/25)	2X 15mm	Polyurethane Grey	330	145 (5-7/10)	100.5 (3-61/64)	Double Precision Ball	PL-05PYP-283-TL-CL__
150 (5-9/10)	2X 15mm	Polyurethane Grey	330	165 (6-1/2)	120 (4-3/4)	Double Precision Ball	PL-06PYP-283-TL-CL__

CENTRAL LOCKING DIRECTIONAL AND TOTAL LOCK COMBO

125 (4-21/25)	2X 15mm	Polyurethane Grey	330	145 (5-7/10)	100.5 (3-61/64)	Double Precision Ball	PL-05PYP-283-DT-CL__
150 (5-9/10)	2X 15mm	Polyurethane Grey	330	165 (6-1/2)	120 (4-3/4)	Double Precision Ball	PL-06PYP-283-DT-CL__

FREE SWIVEL MODELS

125 (4-21/25)	2X 15mm	Polyurethane Grey	330	145 (5-7/10)	100.5 (3-61/64)	Double Precision Ball	PL-05PYP-283-SW-CL__
150 (5-9/10)	2X 15mm	Polyurethane Grey	330	165 (6-1/2)	120 (4-3/4)	Double Precision Ball	PL-06PYP-283-SW-CL__

*For Antistatic caster models replace PYP in part number with APP.

Locking Models

M8 threaded holes for fitting either in the direction of travel or 90 degrees to direction of travel

CL01

45° 45°
27.8/27.7 mm Dia.
15° free
1mm hex
98mm
79mm
50mm
4 M8 Mtg. Holes

CL02

M6 threaded holes for fitting either in the direction of travel.

32mm Dia.
30° 30°
54mm
34mm
7mm

Steering (locks swivel)

Free swivel
Locks wheel and swivel

Free Swivel Models

RS03

27.8mm x 45mm for tubular frame with 28mm ID

RS05

32mm x 45mm For tubular frame with 32mm ID

