

# TWIN-MED (TM)

## THREADED STEM MODELS

FREE SWIVEL • BRAKE



- APPLICATIONS**
- Nursing Home Beds
  - Medical Carts
  - Diagnostic Equipment
  - Electronic Equipment
  - Patient Aids
  - Patient Lifts

- FEATURES**
- Ball bearing swivel raceway on 3" and 4" models
  - 5" models feature a sealed precision ball bearing in the swivel raceway
  - Wheels have easy rollability
  - Our design protects axle/bearing areas from hair/water
  - Total Lock models lock both the wheel and swivel
  - Directional Lock (locks swivel) models are available. Please consult factory.

Special colors available. Consult factory.

New Flexthane softer urethane tread available. To order change PYP to FYP in wheel code (Example: TM-03FYP-281-SW-TS02).



### FREE SWIVEL MODELS

Wheel Diameter (Inches)	Tread Width Inches (mm)	Wheel Description	Capacity (lbs)	Load Height Inches (mm)	Swivel Radius Inches (mm)	Wheel Bearing	Model Number
3	2-5/16" (59)	Polyurethane Gray	165	3-3/4" (95)	2-7/16" (65)	Plain	TM-03PY0-281-SW-____
3	2-5/16" (59)	Polyurethane Gray	165	3-3/4" (95)	2-7/16" (65)	Precision	TM-03PYP-281-SW-____
4	2-39/64" (66)	Polyurethane Gray	220	5" (127)	3-1/8" (79)	Plain	TM-04PY0-281-SW-____
4	2-39/64" (66)	Polyurethane Gray	220	5" (127)	3-1/8" (79)	Precision	TM-04PYP-281-SW-____
4	2-39/64" (66)	Thermoplastic TPP	220	5" (127)	3-1/8" (79)	Plain	TM-04TPO-281-SW-____
5	3" (76)	Polyurethane Gray	246	6" (152)	4" (102)	Precision	TM-05PYP-281-SW-____
5	3" (76)	Thermoplastic TPP	246	6" (152)	4" (102)	Precision	TM-05TPP-281-SW-____

Total Lock (Grey Pedal)



### TOTAL LOCK MODELS (LOCKS WHEEL AND SWIVEL)

Wheel Diameter (Inches)	Tread Width Inches (mm)	Wheel Description	Capacity (lbs)	Load Height Inches (mm)	Swivel Radius Inches (mm)	Wheel Bearing	Model Number
3	2-5/16" (59)	Polyurethane Gray	165	3-3/4" (95)	2-7/16" (65)	Plain	TM-03PY0-281-TL-____
3	2-5/16" (59)	Polyurethane Gray	165	3-3/4" (95)	2-7/16" (65)	Precision	TM-03PYP-281-TL-____
4	2-39/64" (66)	Polyurethane Gray	220	5" (127)	3-1/8" (79)	Plain	TM-04PY0-281-TL-____
4	2-39/64" (66)	Polyurethane Gray	220	5" (127)	3-1/8" (79)	Precision	TM-04PYP-281-TL-____
4	2-39/64" (66)	Thermoplastic TPP	220	5" (127)	3-1/8" (79)	Plain	TM-04TPO-281-TL-____
5	3" (76)	Polyurethane Gray	246	6" (152)	4" (102)	Precision	TM-05PYP-281-TL-____
5	3" (76)	Thermoplastic TPP	246	6" (152)	4" (102)	Precision	TM-05TPP-281-TL-____


### THREADED STEM FITTINGS

See fittings page for more options.

TS02

TS15

TS18



3" diameter models only

Specify Threaded Stem (TS) code, see fittings below for dimensions:



# TWIN-MED (TM)

## TOP PLATE MODELS

FREE SWIVEL • BRAKE



### APPLICATIONS

- Nursing Home Beds
- Medical Carts
- Diagnostic Equipment
- Electronic Equipment
- Patient Aids
- Patient Lifts

### FEATURES

- Ball bearing swivel raceway on 3" and 4" models
- 5" models feature a sealed precision ball bearing in the swivel raceway
- Wheels have easy rollability
- Our design protects axle/bearing areas from hair/water
- Total Lock models lock both the wheel and swivel
- Directional Lock (locks swivel) models are available. Please consult factory.

Special colors available. Consult factory.

New Flexthane softer urethane tread available. To order change PYP to FYP in wheel code (Example: TM-03FYP-281-SW-TS02).



## FREE SWIVEL MODELS

Wheel Diameter (Inches)	Tread Width Inches (mm)	Wheel Description	Capacity (Lbs)	Load Height Inches (mm)	Swivel Radius Inches (mm)	Wheel Bearing	Model Number
3	2-5/16 (59)	Polyurethane Gray	165	4-1/8" (105)	2-5/16" (59)	Plain	TM-03PYO-281-SW-____
3	2-5/16 (59)	Polyurethane Gray	165	4-1/8" (105)	2-5/16" (59)	Precision	TM-03PYP-281-SW-____
4	2-39/64" (66)	Polyurethane Gray	220	5-3/8" (137)	3-1/8" (79)	Plain	TM-04PYO-281-SW-____
4	2-39/64" (66)	Polyurethane Gray	220	5-3/8" (137)	3-1/8" (79)	Precision	TM-04PYP-281-SW-____
4	2-39/64" (66)	Thermoplastic TPP	220	5-3/8" (137)	3-1/8" (79)	Plain	TM-04TPO-281-SW-____
5	3" (76)	Polyurethane Gray	246	6-3/8" (162)	4" (102)	Precision	TM-05PYP-281-SW-____
5	3" (76)	Thermoplastic TPP	246	6-3/8" (162)	4" (102)	Precision	TM-05TPP-281-SW-____





## TOTAL LOCK MODELS (LOCKS WHEEL AND SWIVEL)

Wheel Diameter (Inches)	Tread Width Inches (mm)	Wheel Description	Capacity (Lbs)	Load Height Inches (mm)	Swivel Radius Inches (mm)	Wheel Bearing	Model Number
3	2-5/16 (59)	Polyurethane Gray	165	4-1/8" (105)	2-5/16" (59)	Plain	TM-03PYO-281-TL-____
3	2-5/16 (59)	Polyurethane Gray	165	4-1/8" (105)	2-5/16" (59)	Precision	TM-03PYP-281-TL-____
4	2-39/64" (66)	Polyurethane Gray	220	5-3/8" (137)	3-1/8" (79)	Plain	TM-04PYO-281-TL-____
4	2-39/64" (66)	Polyurethane Gray	220	5-3/8" (137)	3-1/8" (79)	Precision	TM-04PYP-281-TL-____
4	2-39/64" (66)	Thermoplastic TPP	220	5-3/8" (137)	3-1/8" (79)	Plain	TM-04TPO-281-TL-____
5	3" (76)	Polyurethane Gray	246	6-3/8" (162)	4" (102)	Precision	TM-05PYP-281-TL-____
5	3" (76)	Thermoplastic TPP	246	6-3/8" (162)	4" (102)	Precision	TM-05TPP-281-TL-____

## TOP PLATE FITTINGS

See fittings page for more options.



\*Change "TL" to "DL" for Direction Lock models. Available on all precision bearing models. TM-04PYP-281-DL-TP01 shown.

